

## **Powder-Free Nitrile Gloves** (ASTM) Specifications

#### **Product Specification**

Product Type Powder-Free, Non-sterile, Single-use Nitrile Butadiene Rubber (NBR) Material Black, Blue, White XS, S, M, L, XL Weight (g) 2.5 ± 0.2 Not made with natural rubber latex
 Ambidextrous Design & Features Finger Textured
 Beaded cuff

### Quality Standards

Manufactured under ISO 9001:2015 and ISO 13485:2016 Quality Management System

3 years from the date of manufacturing

Food Contact

Shelf-life

Conforms to Personal Protective Equipment Regulation (EU) 2016/425 Category I

Conforms to Federal Legislation US FDA 21 CFR 177.2600
Conforms to Regulation (EU) No 1935/2004
(Italian D.M. 21/03/73, EC Directive 93/11/EEC & Council of Europe Resolution AP(2004)4)

Conforms to JETRO and Korea MFDS standards

# 2.5g Black | Blue | White **Powder-Free Nitrile Gloves**

### Physical Properties

PROPERTY	ASTM D6319		
	Before Aging	After Aging	
Tensile Strength (MPa)	Min 14	Min 14	
Elongation at Break (%)	Min 500	Min 400	
Powder Content (mg/glove)	≤ 2.0		

### **Physical Dimension**

DIMENSIONS Length (mm)		STANDARDS			
		One Glove	ASTM D6319	EN455	
		Min 240	Min 220 (XS, S), Min 230 (M, L, XL)	Min 240	
Palm Width	XS	75 ± 5	70 ± 10	≤80	
(mm)	S	85 ± 5	80 ± 10	80 ± 10	
	М	95 ± 5	95 ± 10	95 ± 10	
	L	105 ± 5	110 ± 10	110 ± 10	
	XL	115 ± 5	120 ± 10	≥110	

Single Wall Thickness (mm)			
Finger (13 ± 3 mm from finger tip)	Min 0.06		
Palm (33 ± 5 mm from crotch)	Min 0.04		
*Cuff (25 ± 5 mm from cuff edge)	Min 0.03		

### Quality Assurance for Pre-Shipment Inspection

Characteristic	Dimension	Physical Properties	Freedom from Holes	Visual Defects	
				Major	Minor
Inspection Level	S2	S2	G1	G1	G1
AQL	4.0	4.0	4.0	2.5	4.0

<sup>\*</sup>This pre-shipment inspection follows our standard guidelines and is subjected to change according to agreed requirements and specifications. For further information, please contact our sales team.











