



Ultraviolet 3.2g Nitrile Powder Free Examination Glove

Nitrile Powder Free Examination Glove (ASTM & EN)

pecification	
N032ULV-CS-24FT	
Non-Sterile, Powder-Free, Nitrile, Ambidextrous, Examination Glove	
Ultraviolet	
Medical use - for medical examinations and procedures to help prevent contamination between healthcare workers and patients.	
This product meets the current version of ASTM D6319, EN 455-1,2,3 and 4, and Customer Requirements / Category I - PPE (EU 2016/425) / EN ISO 21420:2020 / Food Contact: UNI EN1186, EN13130. This product is also manufactured in accordance with a quality management system that conforms to ISO 9001 and ISO 13485.	
Nitrile Butadiene Rubber	
Beaded	
Finger Textured	
Other requirements, including labelling and packaging, is subject to customer and market regulatory requirements and is specified in the Customer Product Sheet.	
A Certificate of Release is available upon request to ensure all products confirm to specification.	

Requirement: PAH content per EN ISO 21420:2020	< 0.2 mg/kg (of each PAH listed in the appendices)	Pass
Requirement: REACH 1907/2006 annex XV II entry number 50	< 0.01% (w/w) of each SVHC Candidate List	Pass

Physical Dimension

Size	xs	s	М	L	XL
Palm Width (mm)	75 ± 5	85 ± 5	95 ± 5	105 ± 5	115 ± 5
Length (mm) (min.)	240 mm				
Weight (g)	3.2 ± 0.3 g				
Location of Thickness Measurement	Single Wall (mm)				
~ Cuff (25 \pm 5 mm from cuff edge)	≥ 0.04				
~ Palm (33 ± 5 mm from crotch)	≥ 0.05				
~ Finger (13 ± 3 mm from fingertip)	≥ 0.06				

Physical Properties

Criteria	Before Aging	After Aging
Tensile Strength (Mpa) (min.)	14	14
Elongation (%) (min.)	500	400
Force at Break (N) (Median)	6	6

Pre-shipment Inspection

Characteristic	Dimension	Physical Properties	Freedom	Visual Defects	
	Dimension		Properties from Holes	Major	Minor
Inspection Level	S2	S2	G1	G1	G1
AQL	4.0	4.0	1.5	2.5	4.0













